

EWP64-65, HELIAX® Premium Elliptical Waveguide, 6.425–7.125 GHz, unjacketed

## Product Classification

<b>Brand</b>	HELIAX®
<b>Product Type</b>	Elliptical waveguide

## Construction Materials

<b>Jacket Material</b>	Unjacketed
<b>Conductor Material</b>	Corrugated copper

## Dimensions

<b>Cable Volume</b>	725.0 L/km   7.8 ft <sup>3</sup> /kft
<b>Cable Weight</b>	0.73 kg/m   0.49 lb/ft
<b>Diameter Over Jacket (E Plane)</b>	48.50 mm   1.91 in
<b>Diameter Over Jacket (H Plane)</b>	28.40 mm   1.12 in

## Electrical Specifications

<b>Operating Frequency Band</b>	6.425 – 7.125 GHz
<b>eTE11 Mode Cutoff</b>	4.320 GHz
<b>Group Delay</b>	125 ns/100 ft @ 7.400 GHz 411 ns/100 m @ 7.400 GHz

## Environmental Specifications

<b>Installation Temperature</b>	-40 °C to +60 °C (-40 °F to +140 °F)
<b>Operating Temperature</b>	-55 °C to +85 °C (-67 °F to +185 °F)
<b>Storage Temperature</b>	-70 °C to +85 °C (-94 °F to +185 °F)

## Mechanical Specifications

<b>Maximum Twist</b>	3.00 %/m   1.00 %/ft
<b>Minimum Bend Radius, Multiple Bends (E Plane)</b>	260.00 mm   10.00 in
<b>Minimum Bend Radius, Multiple Bends (H Plane)</b>	685.00 mm   27.00 in
<b>Minimum Bend Radius, Single Bend (E Plane)</b>	260.00 mm   10.00 in
<b>Minimum Bend Radius, Single Bend (H Plane)</b>	685.00 mm   27.00 in

## Note

<b>Performance Note</b>	Values typical, unless otherwise stated
-------------------------	---

## Standard Conditions

<b>Attenuation, Ambient Temperature</b>	24 °C   75 °F
<b>Average Power, Ambient Temperature</b>	40 °C   104 °F
<b>Average Power, Temperature Rise</b>	42 °C   76 °F

## Return Loss/VSWR

Frequency Band	VSWR	Return Loss (dB)
6.425–7.125 GHz	1.06	30.70

\* VSWR/Return Loss indicated is for lengths up to 300 ft (91.4 m)

\* VSWR/Return Loss is guaranteed for factory-fit and typical for field-fit assemblies

\* Custom length performance: Call 828-324-2200 or 1-800-982-1708 (toll free), or your local CommScope representative

## Attenuation

Frequency (GHz)	Attenuation (dB/100 ft)	Attenuation (dB/100 m)	Average Power (kW)	Group Velocity %
6.4	1.608	5.276	3.917	74
6.6	1.568	5.145	4.017	75.8
6.8	1.534	5.033	4.107	77.4
7	1.505	4.938	4.186	78.8

## Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
China RoHS SJ/T 11364-2014	Below Maximum Concentration Value (MCV)

