# 760258039 | HCA-ACC-3mm SC/APC Test Lead



# HCA-ACC-3mm SC/APC Test Lead 50FT, Full size, DLX and Bayonet converter include5

• Prodigy converters simplify installation and maintenance by reducing splicing requirements in the distribution portion of the network

| Regional Availability           | North America         |
|---------------------------------|-----------------------|
| Product Type                    | Fiber test patch cord |
| Product Brand                   | PRODIGY™              |
| Product Series                  | HCA                   |
| General Specifications          |                       |
| Color, boot A                   | Black                 |
| Color, connector A              | Black                 |
| Color, connector B              | Green                 |
| Interface, Connector A          | Prodigy               |
| Interface, Connector B          | SC/APC                |
| Jacket Color                    | Yellow                |
| Dimensions                      |                       |
| Cable Assembly Length           | 15.24 m   50 ft       |
| Mechanical Specifications       |                       |
| Dust Cap Pulling Force, minimum | 445 N   100.04 lbf    |
| Optical Specifications          |                       |
| Insertion Loss, maximum         | 0.3 dB                |
| Insertion Loss, typical         | 0.15 dB               |
| Return Loss, minimum            | 65 dB                 |

#### **Environmental Specifications**

#### **Operating Temperature**

-40 °C to +70 °C (-40 °F to +158 °F)

Page 1 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: December 27, 2024



### 760258039 50FT, 3x Cvtr

## 760258039 | HCA-ACC-3mm SC/APC Test Lead

Storage Temperature

**Environmental Space** 

**Qualification Standards** 

-40 °C to +70 °C (-40 °F to +158 °F) Indoor/Outdoor IEC 60793 | IEC 60794

Page 2 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: December 27, 2024

