


# LDF6RN-50

LDF6-50, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1-1/4 in, gray non-halogenated, fire retardant polyolefin jacket



## OBSOLETE

This product was discontinued on: May 21, 2017

### Replaced By:

AVA6RK-50	AVA6RK-50, HELIAX® Andrew Virtual Air™ Coaxial Cable, corrugated copper, 1-1/4 in, black , fire retardant polyolefin jacket B2ca- s1b, d2,a1 (CPR testing is conducted annually please reference the website for latest classification)
AVA6RKD-50	AVA6-50, HELIAX® Andrew Virtual Air™ Coaxial Cable, corrugated copper, 1-1/4 in, black , fire retardant polyolefin jacket

## Product Classification

<b>Product Type</b>	Coaxial wireless cable
<b>Product Brand</b>	HELIAX®
<b>Product Series</b>	LDF6-50

## General Specifications

<b>Flexibility</b>	Standard
<b>Jacket Color</b>	Gray
<b>Performance Note</b>	Attenuation values typical, guaranteed within 5%

## Dimensions

<b>Diameter Over Dielectric</b>	33.782 mm   1.33 in
<b>Diameter Over Jacket</b>	39.37 mm   1.55 in
<b>Inner Conductor OD</b>	13.208 mm   0.52 in
<b>Outer Conductor OD</b>	35.814 mm   1.41 in
<b>Nominal Size</b>	1-1/4 in

# LDF6RN-50

## Electrical Specifications

<b>Cable Impedance</b>	50 ohm $\pm$ 1 ohm
<b>Capacitance</b>	75.1 pF/m   22.89 pF/ft
<b>dc Resistance, Inner Conductor</b>	0.722 ohms/km   0.22 ohms/kft
<b>dc Resistance, Outer Conductor</b>	0.623 ohms/km   0.19 ohms/kft
<b>dc Test Voltage</b>	9000 V
<b>Inductance</b>	0.184 $\mu$ H/m   0.056 $\mu$ H/ft
<b>Insulation Resistance</b>	100000 MOhms-km
<b>Jacket Spark Test Voltage (rms)</b>	8000 V
<b>Operating Frequency Band</b>	1 – 3300 MHz
<b>Peak Power</b>	205 kW
<b>Velocity</b>	89 %

## Attenuation

<b>Frequency (MHz)</b>	<b>Attenuation (dB/100 m)</b>	<b>Attenuation (dB/100 ft)</b>	<b>Average Power (kW)</b>
1.0	0.075	0.023	127.47
1.5	0.092	0.028	103.94
2.0	0.107	0.033	89.92
10.0	0.241	0.074	39.81
20.0	0.344	0.105	27.94
30.0	0.423	0.129	22.69
50.0	0.551	0.168	17.42
85.0	0.728	0.222	13.2
88.0	0.741	0.226	12.96
100.0	0.792	0.242	12.12
108.0	0.825	0.252	11.64
150.0	0.983	0.299	9.77
174.0	1.064	0.324	9.03
200.0	1.146	0.349	8.38
204.0	1.158	0.353	8.29
300.0	1.428	0.435	6.73
400.0	1.672	0.51	5.74
450.0	1.784	0.544	5.38
460.0	1.806	0.551	5.32

# LDF6RN-50

---

500.0	1.892	0.577	5.08
512.0	1.917	0.584	5.01
600.0	2.095	0.639	4.58
700.0	2.286	0.697	4.2
800.0	2.466	0.752	3.89
824.0	2.508	0.764	3.83
894.0	2.628	0.801	3.65
960.0	2.738	0.834	3.51
1000.0	2.803	0.854	3.43
1218.0	3.143	0.958	3.06
1250.0	3.191	0.973	3.01
1500.0	3.553	1.083	2.7
1700.0	3.827	1.166	2.51
1794.0	3.952	1.204	2.43
1800.0	3.96	1.207	2.43
2000.0	4.219	1.286	2.28
2100.0	4.345	1.324	2.21
2200.0	4.469	1.362	2.15
2300.0	4.591	1.399	2.09
2500.0	4.831	1.472	1.99
2700.0	5.065	1.544	1.9
3000.0	5.406	1.648	1.78

## Material Specifications

<b>Dielectric Material</b>	Foam PE
<b>Jacket Material</b>	Non-halogenated, fire retardant polyolefin
<b>Inner Conductor Material</b>	Copper tube
<b>Outer Conductor Material</b>	Corrugated copper

## Mechanical Specifications

<b>Minimum Bend Radius, multiple Bends</b>	381 mm   15 in
<b>Minimum Bend Radius, single Bend</b>	152.4 mm   6 in
<b>Number of Bends, minimum</b>	15
<b>Number of Bends, typical</b>	40
<b>Tensile Strength</b>	590 kg   1,300.726 lb

# LDF6RN-50

---

<b>Bending Moment</b>	48.8 N-m   431.916 in lb
<b>Flat Plate Crush Strength</b>	2.2 kg/mm   123.194 lb/in

## Environmental Specifications

<b>Installation temperature</b>	-25 °C to +60 °C (-13 °F to +140 °F)
<b>Operating Temperature</b>	-30 °C to +80 °C (-22 °F to +176 °F)
<b>Storage Temperature</b>	-30 °C to +80 °C (-22 °F to +176 °F)
<b>Attenuation, Ambient Temperature</b>	68 °F   20 °C
<b>Average Power, Ambient Temperature</b>	104 °F   40 °C
<b>Average Power, Inner Conductor Temperature</b>	212 °F   100 °C
<b>Fire Retardancy Test Method</b>	UL 1666/CATVR
<b>Smoke Index Test Method</b>	IEC 61034
<b>Toxicity Index Test Method</b>	IEC 60754-1   IEC 60754-2

## Packaging and Weights

<b>Cable weight</b>	0.94 kg/m   0.632 lb/ft
---------------------	-------------------------

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
UL/ETL Certification	CATVR

