760066183 | iP-PTF-12-SC-OS

iPatch® Pre-Terminated OptiSPEED® Intelligent Fiber Panel, SC 12 port duplex

Product Classification

Regional Availability	Asia	Australia/New Zealand	EMEA	Latin America	North America
Portfolio	CommScope®
Product Type	Fiber splice panel
Product Brand	OptiSPEED®	iPatch®

General Specifications

Color	Black
Intelligence Type	iPatch® enabled
Interface, front	SC
Rack Units	1
Shelf Movement	Sliding
Total Ports, quantity	12

Dimensions

Height	44.45 mm	1.75 in
Width	482.6 mm	19 in
Depth	323.85 mm	12.75 in

Material Specifications

Material Type	Acrylonitrile butadiene styrene (ABS)	Polycarbonate (PC)

Optical Specifications

Fiber Mode	Multimode

Environmental Specifications

COMMSCOPE®

760066183 | iP-PTF-12-SC-OS

Operating Temperature	-5 °C to +50 °C (+23 °F to +122 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	Up to 95%, non-condensing
Flammability Rating	UL 94 V-0
Safety Standard	ACMA	CE	CSA	UL

Packaging and Weights

Included	Four #12-24 mounting screws	Instruction sheet	Shelf
Packaging quantity	1
Weight, net	3.175 kg	7 lb

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

COMMSCOPE®