760051193 | 1100GS5-DM Distribution Module Kit



GigaSPEED X10D® 1100GS5 Category 6A U/UTP Patch Panel Distribution Module Kit

OBSOLETE

This product was discontinued on: July 1, 2011

Replaced By:

760105296 1100-GS6-DM

GigaSPEED X10D® 1100GS6 Category 6A U/UTP Distribution Module, 6 port

760151183

360-IPR-1100-GS6-DM6

SYSTIMAX 360™ GigaSPEED X10D® 1100GS6 Evolve Category 6A U/UTP Distribution Module, 6 port

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin

America | North America

Portfolio SYSTIMAX®

Product Type Module

Product Brand GigaSPEED X10D®

General Specifications

ANSI/TIA Category 6A

Cable Type Unshielded

Color Black

Conductor Type Solid | Stranded

Intelligence Type Passive

Modules, quantity 1

Termination Type IDC

Total Ports, quantity 6

Wiring T568A | T568B

Dimensions

Compatible Diameter Over Dielectric, maximum1.168 mm | 0.046 inCompatible Diameter Over Dielectric, minimum0.762 mm | 0.03 in

Page 1 of 2



760051193 | 1100GS5-DM Distribution Module Kit

Compatible Conductor Gauge, solid22 AWG24 AWGCompatible Conductor Gauge, stranded22 AWG24 AWG

Electrical Specifications

Current Rating at Temperature 1.5 A @ 20 °C | 1.5 A @ 68 °F

Dielectric Withstand Voltage, RMS, conductive surface1,500 Vac @ 60 HzDielectric Withstand Voltage, RMS, contact-to-contact1,000 Vac @ 60 Hz

Insulation Resistance, minimum 500 MOhm

Material Specifications

Contact Plating Material Precious metals

Material Type High-impact, flame retardant, thermoplastic

Termination Contact Plating Nickel

Mechanical Specifications

Plug Insertion Life, minimum 750 times

Plug Insertion Life, test plug IEC 60603-7 compliant plug

Plug Retention Force, minimum 133.447 N | 30 lbf

Environmental Specifications

Operating Temperature $-10 \,^{\circ}\text{C}$ to $+60 \,^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +140 $^{\circ}\text{F}$)Storage Temperature $-40 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ (-40 $^{\circ}\text{F}$ to +158 $^{\circ}\text{F}$)

Relative Humidity Up to 95%, non-condensing

Flammability Rating UL 94 V-0
Safety Standard UL | cUL

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

ISO

