NG4-VCMR2F47002K



NG4access® Module VAM, CWDM, 8 channels, 1310 nm port, 2 circuits, LC/APC, right, 1471 nm starting channel, 2 test ports

- VAMs help enhance optical transport systems by providing flexible, easy to incorporate optical components into the network
- VAMs increase fiber capacity and help troubleshooting or distributing signals to multiple subscribers

Product Classification

Regional Availability Latin America | North America

Product Type CWDM module
Product Brand NG4access®

Product Series NG4

General Specifications

Device Type Plug-and-play module

Functionality Multiplexing

Application For use with NG4 access frames

Circuits, quantity 2

Distribution Type 8-channel CWDM

Interface, frontLC/APCInterface, InputLC/APCInterface, OutputLC/APC

Multiplexers, quantity 2

Port Type, optional 1310 nm port | Test port

Tray Orientation Right orientation

Dimensions

 Height
 13.21 mm | 0.52 in

 Width
 159.77 mm | 6.29 in

 Depth
 130.3 mm | 5.13 in



NG4-VCMR2F47002K

Optical Specifications

Starting Channel Number 47

Starting Wavelength 1471 nm

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant

