OTE200-06MX-NN-S12-G-W



Mini-OTE 200-Series, Optical Terminal Enclosure, 6-port mini-size connector (DLX®), no splitter, gray, wall mount

- Optical Terminal Enclosures incorporate hardened connector technology that is designed to withstand the rugged outside plant environment
- Functionality to splice and store feeder cable in the field with the possibility to splice in the field two extra branch cables
- Hardened adapters are factory-terminated and environmentally sealed to ensure rapid plug-and play drop cable installations
- Integrated external cable fixation guarantees easy, fast and reliable cable manipulations

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America

Product Type Access terminal, without splitter/tap

Product Brand DLX®

Product Series Mini-OTE 200

General Specifications

Cable, quantity 0

Distribution Type 6 ports

Enclosure Color Gray

Mounting Handhole | Pole | Wall

Port Type Hardened mini-size DLX

Port, quantity 6
Splitter, quantity 0

Stub Type No tail

Dimensions

 Height
 358.5 mm | 14.114 in


 Width
 166 mm | 6.535 in


 Depth
 129.3 mm | 5.091 in


Dimension Drawing




OTE200-06MX-NN-S12-G-W







Ordering Tree



Material Specifications

Enclosure Material Type Glass filled polypropylene (GF-PP)

Optical Specifications

Fiber Type G.652.D

Wavelength Range 1260–1635 nm

Insertion Loss, Terminal Connector, maximum 0.4 dB

COMMSCOPE®

OTE200-06MX-NN-S12-G-W

Insertion Loss, Terminal Connector, typical0.16 dBReturn Loss, Connector, minimum65 dB

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C}$ to $+65 \,^{\circ}\text{C}$ ($-40 \,^{\circ}\text{F}$ to $+149 \,^{\circ}\text{F}$)

Relative Humidity 5%-100%, condensing

Environmental Space Above ground | Below ground | Buried

Qualification Standards IEC 60529, IP68 + 3 m waterhead

UV Resistance UV stabilized

Packaging and Weights

Included Cable termination unit (2) | Enclosure (1) | Fiber pigtail cassette

(1) | Splice Cassette (2)

Packaging quantity

Packaging Type Box | Carton

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



Included Products

TENIO-CTU-L-(10)

CW8094-002 - TENIO™ Cable Termination Unit kit



CW8094-002 | TENIO-CTU-L-(10)





Product Classification

Regional Availability EMEA

Product Type Cable termination kit

Product Series TENIO

Environmental Specifications

Environmental Space Outdoor

Packaging and Weights

Packaging quantity

Packaging Type Bag | Carton

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant

