

Sigma-Link™ Universal Connectivity Platform Q-Fit Cable Assembly, RJ45 to RJ45, Class Fa, S/FTP, white, 15 m

- Sigma-Link is a pre-terminated factory-tested copper system for networking infrastructures and guarantees a 100% throughput performance
- Sigma-Link cable assemblies are offered in Housing-to-Housing, Housing-to-Jacks, Housing-to-Plugs and Housing to stub tail configurations
- Ranging from Category 6 to Category 7A, Sigma-Link supports up to 10GbE (10 Gigabit Ethernet) transmission and beyond
- Housing-to-Housing version features integrated Plastic Optical Fiber (POF) for easy tracing of far end

OBSOLETE

This product was discontinued on: October 10, 2017

Product Classification

| Regional Availability | Asia Australia/New Zealand EMEA | |
|--------------------------------|-------------------------------------|--|
| Portfolio | NETCONNECT® | |
| Product Type | Copper trunk cable assembly | |
| Product Brand | Sigma-Link™ | |
| Product Series | Sigma-Link UCP | |
| General Specifications | | |
| ANSI/TIA Category | 6A | |
| Cable Type | S/FTP (shielded) | |
| Conductor Type | Solid | |
| Interface, Connector A | RJ45 plug | |
| Interface Feature, connector A | Standard | |
| Interface, Connector B | RJ45 plug | |
| Interface Feature, connector B | Standard | |
| Jacket Color | White | |
| Link Count | 6 | |
| Transmission Standards | ISO/IEC 11801 Class EA | |

Dimensions

Page 1 of 2

©2021 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: November 4, 2020



1-1711771-5

Cord Length

15 m | 49.213 ft

Material Specifications

| Conductor Material | Bare copper |
|--------------------|-------------|
|--------------------|-------------|

Environmental Specifications

| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |
|-----------------------|--|
| Storage Temperature | -20 °C to +80 °C (-4 °F to +176 °F) |
| Environmental Space | Low Smoke Fire Retardant Zero Halogen (LSFRZH) |

Packaging and Weights

Packaging quantity

1

Regulatory Compliance/Certifications

| Agency | Classification |
|------------|---|
| CHINA-ROHS | Below maximum concentration value |
| REACH-SVHC | Compliant as per SVHC revision on www.commscope.com/ProductCompliance |
| ROHS | Compliant |
| | |

Page 2 of 2

©2021 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: November 4, 2020

