

# F4-DMDM-4-D

---



D-CLASS HELIAX® 1/2" SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male, 4 ft

## Product Classification

|                       |                                |
|-----------------------|--------------------------------|
| <b>Product Type</b>   | SureFlex® D-CLASS, dynamic PIM |
| <b>Product Brand</b>  | HELIAX®   SureFlex®            |
| <b>Product Series</b> | RSJ4-50                        |

## General Specifications

|   |               |
|---|---------------|
| <b>Body Style, Connector A</b>            | Straight      |
| <b>Body Style, Connector B</b>            | Straight      |
| <b>Interface, Connector A</b>             | 7-16 DIN Male |
| <b>Interface, Connector B</b>             | 7-16 DIN Male |
| <b>Specification Sheet Revision Level</b> | A             |

## Dimensions

|                     |                    |
|---------------------|--------------------|
| <b>Length</b>       | 1.219 m   3.999 ft |
| <b>Nominal Size</b> | 1/2 in             |

## Logo Image

# F4-DMDM-4-D



## Electrical Specifications

|  |                                    |
|--|------------------------------------|
| <b>3rd Order IMD Dynamic</b>             | -116 dBm                           |
| <b>3rd Order IMD Dynamic Test Method</b> | Two +43 dBm carriers per IEC 62037 |
| <b>DTF, Connector A</b>                  | -34 dB                             |
| <b>DTF, Connector B</b>                  | -34 dB                             |

## VSWR/Return Loss

| <b>Frequency Band</b> | <b>VSWR</b> | <b>Return Loss (dB)</b> |
|-----------------------|-------------|-------------------------|
| <b>698–960 MHz</b>    | 1.065       | 30.04                   |
| <b>1700–2200 MHz</b>  | 1.065       | 30.04                   |
| <b>2200–2700 MHz</b>  | 1.106       | 25.96                   |
| <b>3400–3800 MHz</b>  | 1.222       | 20.01                   |

## Jumper Assembly Sample Label

# F4-DMDM-4-D

---



## Environmental Specifications

**Immersion Test Method** Meets IEC 60529:2001, IP68 in mated condition

## Regulatory Compliance/Certifications

| Agency        | Classification   |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |