

NNVV-65B-R4

8-port sector antenna, 4x 698–896 and 4x 1695–2690 MHz, 65° HPBW, 4x RET



- Uses the 4.3-10 connector which is 40 percent smaller than the 7-16 DIN connector
- All internal RET actuators are connected in “Cascaded MRET” configuration

OBSOLETE

This product was discontinued on: **March 31, 2021**

Replaced By:

RRVV-65B-R4-V2 8-port sector antenna, 4x 694–960 and 4x 1695–2690 MHz, 65° HPBW, 4x RET

General Specifications

Antenna Type	Sector
Band	Multiband
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage Wind loading figures are validated by wind tunnel measurements described in white paper WP-112534-EN
Radome Material	Fiberglass, UV resistant
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	4
RF Connector Quantity, low band	4
RF Connector Quantity, total	8

Remote Electrical Tilt (RET) Information

RET Hardware	CommRET v2
RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	1 female 1 male

NNVV-65B-R4

Input Voltage	10–30 Vdc
Internal RET	High band (2) Low band (2)
Power Consumption, idle state, maximum	1 W
Power Consumption, normal conditions, maximum	8 W
Protocol	3GPP/AISG 2.0 (Multi-RET)

Dimensions

Width	498 mm 19.606 in
Depth	197 mm 7.756 in
Length	1828 mm 71.969 in
Net Weight, without mounting kit	35.1 kg 77.382 lb

Array Layout



Array	Freq (MHz)	Conns	RET (MRET)	AISG RET UID
R1	698-896	1-2	1	CPxxxxxxxxxxxxxxxxmm.1
R2	698-896	3-4	2	CPxxxxxxxxxxxxxxxxmm.2
Y1	1695-2690	5-6	3	CPxxxxxxxxxxxxxxxxmm.3
Y2	1695-2690	7-8	4	CPxxxxxxxxxxxxxxxxmm.4

Left Right
Bottom

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration

NNVV-65B-R4



Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1695 – 2690 MHz 698 – 896 MHz
Polarization	±45°
Total Input Power, maximum	900 W @ 50 °C

Electrical Specifications

Frequency Band, MHz	698–806	806–896	1695–1880	1850–1990	1920–2180	2300–2500	2500–2690
Gain, dBi	14.5	14.9	16.8	17.2	17.5	18.1	17.8
Beamwidth, Horizontal, degrees	66	64	60	60	62	59	64
Beamwidth, Vertical, degrees	11.7	10.4	7.3	6.8	6.4	5.4	5.1
Beam Tilt, degrees	2–14	2–14	2–12	2–12	2–12	2–12	2–12
USLS (First Lobe), dB	16	18	14	16	15	16	18
Front-to-Back Ratio at 180°, dB	31	34	38	38	37	33	30
Isolation, Cross Polarization, dB	25	25	25	25	25	25	25
Isolation, Inter-band, dB	25	25	25	25	25	25	25
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0

NNVV-65B-R4

PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150	-150	-150	-150	-150
Input Power per Port at 50°C, maximum, watts	300	300	250	250	250	200	200

Electrical Specifications, BASTA

Frequency Band, MHz	698-806	806-896	1695-1880	1850-1990	1920-2180	2300-2500	2500-2690
Gain by all Beam Tilts, average, dBi	14.1	14.6	16.5	16.9	17	17.6	17.3
Gain by all Beam Tilts Tolerance, dB	±0.5	±0.5	±0.7	±0.4	±0.5	±0.6	±0.7
Gain by Beam Tilt, average, dBi	2° 14.2 8° 14.2 14° 13.9	2° 14.7 8° 14.7 14° 14.2	2° 16.6 7° 16.7 12° 16.2	2° 16.8 7° 17.1 12° 16.7	2° 16.9 7° 17.2 12° 16.7	2° 17.5 7° 17.9 12° 17.3	2° 16.9 7° 17.5 12° 17.0
Beamwidth, Horizontal Tolerance, degrees	±3.9	±3.9	±5.7	±2.7	±3.1	±7.9	±8
Beamwidth, Vertical Tolerance, degrees	±0.9	±0.8	±0.7	±0.5	±0.6	±0.4	±0.2
USLS, beampeak to 20° above beampeak, dB	16	18	14	15	14	14	14
Front-to-Back Total Power at 180° ± 30°, dB	20	20	31	31	28	28	26
CPR at Boresight, dB	21	20	18	18	19	19	20
CPR at Sector, dB	8	6	8	8	7	8	5

Mechanical Specifications

Wind Loading @ Velocity, frontal	685.0 N @ 150 km/h (154.0 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	232.0 N @ 150 km/h (52.2 lbf @ 150 km/h)
Wind Loading @ Velocity, maximum	889.0 N @ 150 km/h (199.9 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	564.0 N @ 150 km/h (126.8 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	608 mm 23.937 in
Depth, packed	352 mm 13.858 in
Length, packed	2010 mm 79.134 in
Weight, gross	49 kg 108.026 lb

Regulatory Compliance/Certifications

Agency	Classification
---------------	-----------------------

NNVV-65B-R4

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system



Included Products

- BSAMNT-3 - Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance

BSAMNT-3



Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

Product Classification

Product Type Downtilt mounting kit

General Specifications

Application Outdoor

Color Silver

Dimensions

Compatible Diameter, maximum 115 mm | 4.528 in

Compatible Diameter, minimum 60 mm | 2.362 in

Weight, net 6.2 kg | 13.669 lb

Material Specifications

Material Type Galvanized steel

Packaging and Weights

Included Brackets | Hardware

Packaging quantity 1

Weight, gross 6.4 kg | 14.11 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

BSAMNT-3

