CX3199894 | 075G110TB EMPTY DUCT COEX



ConQuest® Empty Conduit, 3/4 in, SDR 11, gray,

 *Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.

Product Classification

Regional AvailabilityNorth AmericaProduct TypeEmpty conduitProduct BrandConQuest®

Government Funding Build America Buy America (BABA) compliant*

General Specifications

Color Gray

Conduit Type Non-toneable

Density Test Method ASTM D792A

 Density, maximum
 0.955 g/cm³ | 0.035 lb/in³

 Density, minimum
 0.941 g/cm³ | 0.034 lb/in³

Design Standard ASTM D3350-05

Wall Type Smooth

Dimensions

Length 304.8 m | 1000 ft

Inner Diameter, nominal21.336 mm | 0.84 inOuter Diameter, nominal26.67 mm | 1.05 in

Wall Thickness Designation SDR 11

Wall Thickness, minimum 2.413 mm | 0.095 in

Nominal Size 3/4 in

Material Specifications

Flexural Modulus, minimum 551.581 N/mm² | 80000 psi

Flexural Property Test Method ASTM D790

COMMSCOPE®

CX3199894 | 075G110TB EMPTY DUCT COEX

Hydrostatic Design BasisNot pressure rated

Hydrostatic Design Test Method ASTM D2837

Material Type High density polyethylene (HDPE)

Melt Flow Rate Test MethodASTM D1238Melt Flow Rate, maximum0.39 g/10 min

Mechanical Specifications

Minimum Bend Radius, unsupported 304.8 mm | 12 in

Tensile Property Test Method ASTM D638

Tensile Strength at yield, minimum 20.684 N/mm² | 3000 psi

Pulling Tension, maximum 274.423 kg | 605 lb

Environmental Specifications

Environmental Stress Crack Resistance Failure rate of 10% within 96 hours
Environmental Stress Test Method ASTM D1693, ESCR Condition B

Packaging and Weights

Weight, net 193.461 kg/km | 130 lb/kft

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



* Footnotes

Environmental Stress Crack Resistance FSCR—Environmental Stress Crack Resistence

