## 1-2291216-1 | KJ610-IV



#### KJ-Series Modular Jack, RJ45, Cat6 Unshielded, Ivory

#### **Product Classification**

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America

Portfolio NETCONNECT®

Product Type Modular jack

Product Series KJ Series

General Specifications

ANSI/TIA Category 6

Cable Type Unshielded

**Color** Ivory

Conductor Type Solid | Stranded

Integrated Dust Cover Type None

Mounting Hubbell® faceplates | Leviton® faceplates | Panduit®

faceplates

Mounting Note Color matches with KJ-style Electric Ivory Faceplates and Surface

Mount Boxes

Outlet Type Keystone

**Termination Tool** 110 Punchdown tool | SL Termination tool

Termination Type IDC

**Transmission Standards** ANSI/TIA-568-C.2 | ISO/IEC 11801 Class E

**Wiring** T568A | T568B

**Dimensions** 

**Panel Cutout, recommended** 14.79 x 19.31 mm (0.58 x 0.76 in)

Panel Thickness, recommended 1.6 mm | 0.063 in

 Height
 16.13 mm | 0.635 in

 Width
 16.48 mm | 0.649 in

**Depth** 30.48 mm | 1.2 in



# 1-2291216-1 | KJ610-IV

Compatible Insulated Conductor Diameter, maximum 1.27 mm | 0.05 in

Contact Plating Thickness1.27 μmCompatible Conductor Gauge, solid24-22 AWGCompatible Conductor Gauge, stranded26-24 AWG

**Electrical Specifications** 

Remote Powering Fully supports the safe delivery of power over LAN cabling described

by IEEE 802.3bt (Type 4) and complies with the unmating under electrical load requirements prescribed by IEC 60512-99-002

**PoE Durability** Supports IEEE 802.3bt Type 4 (90 W) applications greater than 3000

plug to jack mating cycles

Material Specifications

Contact Base Material Beryllium copper

Contact Plating Material Gold

Material Type Polycarbonate

Mechanical Specifications

Plug to Jack Mating Cycles Complies to IEC 60603-7 series

**Environmental Specifications** 

Flammability Rating UL 94 V-0

Packaging and Weights

Packaging quantity 1
Packaging Type Bag

### Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



