## 1-2291216-3 | KJ610-P.WH



KJ-Series Modular Jack, RJ45, Cat6 Unshielded, ProWhite

## Product Classification

Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America
Portfolio	NETCONNECT®
Product Type	Modular jack
Product Series	KJ Series
General Specifications	
ANSI/TIA Category	6
Cable Type	Unshielded
Color	Pro white
Conductor Type	Solid   Stranded
Integrated Dust Cover Type	None
Mounting	Hubbell® faceplates   Leviton® faceplates   Panduit® faceplates
Mounting Note	Color matches with KJ-style Alpine white or Pro white Faceplates and Surface Mount Boxes
Outlet Type	Keystone
Termination Tool	110 Punchdown tool   SL Termination tool
Termination Type	IDC
Transmission Standards	ANSI/TIA-568-C.2   ISO/IEC 11801 Class E
Wiring	T568A   T568B
Dimensions	
Panel Cutout, recommended	14.79 x 19.31 mm (0.58 x 0.76 in)
Panel Thickness, recommended	1.6 mm   0.063 in
Height	16.13 mm   0.635 in
Width	16.48 mm   0.649 in
Depth	30.48 mm   1.2 in

Page 1 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 25, 2024



## 1-2291216-3 | KJ610-P.WH

	•	
Compatible Insulated Con	ductor Diameter, maximum	1.27 mm   0.05 in
Contact Plating Thickness		1.27 μm
Compatible Conductor Ga	uge, solid	24-22 AWG
Compatible Conductor Gauge, stranded		26-24 AWG
Electrical Specifications		
Remote Powering		Fully supports the safe delivery of power over LAN cabling described by IEEE 802.3bt (Type 4) and complies with the unmating under electrical load requirements prescribed by IEC 60512-99-002
PoE Durability		Supports IEEE 802.3bt Type 4 (90 W) applications after 3000 plug to jack mating cycles
Material Specifications		
Contact Base Material		Beryllium copper
<b>Contact Plating Material</b>		Gold
Material Type		Polycarbonate
Mechanical Specifications		
Plug to Jack Mating Cycles		Complies to IEC 60603-7 series
Environmental Specifications		
Flammability Rating		UL 94 V-0
Packaging and Weights		
Packaging quantity		1
Packaging Type		Bag
Regulatory Compliance/Certifications		
Agency	Classification	
CHINA-ROHS	Below maximum concentration value	
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance	
ROHS	Compliant	

**UK-ROHS** 

Compliant

Page 2 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 25, 2024

COMMSCOPE°