

# 1375055-8 | SL110-6-YL



## SL-Series Modular Jack, RJ45, Cat6 Unshielded, Yellow

### OBSOLETE

#### Replaced By:

1375055-YL  
SL110-6-YL

SL-Series Modular Jack, RJ45, Cat6 Unshielded, Yellow

## Product Classification

### Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America

### Portfolio

NETCONNECT®

### Product Type

Modular jack

### Product Series

SL Series

## General Specifications

### ANSI/TIA Category

6

### Cable Type

Unshielded

### Color

Yellow

### Conductor Type

Solid | Stranded

### Integrated Dust Cover Type

None

### Mounting

SL Series faceplates and panels

### Outlet Feature

Inverted jack face

### Outlet Type

Standard

### Termination Punchdowns, minimum

200 times

### Termination Tool

SL Termination tool

### Termination Type

IDC

### Transmission Standards

ANSI/TIA-568.2-D | ISO/IEC 11801 Class E

### Wiring

T568A | T568B

## Dimensions

# 1375055-8 | SL110-6-YL

|   |                                   |
|---|-----------------------------------|
| <b>Panel Cutout, recommended</b>                        | 14.78 x 20.07 mm (0.58 x 0.79 in) |
| <b>Panel Thickness, recommended</b>                     | 1.6 mm   0.063 in                 |
| <b>Height</b>   | 16.13 mm   0.635 in               |
| <b>Width</b>  | 14.48 mm   0.57 in                |
| <b>Depth</b>  | 30.48 mm   1.2 in                 |
| <b>Compatible Cable Diameter, maximum</b>               | 5.8 mm   0.228 in                 |
| <b>Compatible Insulated Conductor Diameter, maximum</b> | 1.45 mm   0.057 in                |
| <b>Contact Plating Thickness</b>                        | 1.27 $\mu$ m                      |
| <b>Compatible Conductor Gauge, solid</b>                | 24–22 AWG                         |
| <b>Compatible Conductor Gauge, stranded</b>             | 26–24 AWG                         |

## Electrical Specifications

|  |  |
|--|--|
| <b>Contact Resistance Variation, maximum</b>                 | 20 mOhm  |
| <b>Contact Resistance, maximum</b>                           | 100 mOhm   |
| <b>Current Rating at Temperature</b>                         | 1.5 A @ 20 °C   1.5 A @ 68 °F  |
| <b>Dielectric Withstand Voltage, RMS, conductive surface</b> | 1,500 Vac @ 60 Hz  |
| <b>Dielectric Withstand Voltage, RMS, contact-to-contact</b> | 1,000 Vac @ 60 Hz  |
| <b>Insulation Resistance, minimum</b>                        | 500 mOhm   |
| <b>Remote Powering</b>                                       | Fully supports the safe delivery of power over LAN cabling described by IEEE 802.3bt (Type 4) and complies with the unmating under electrical load requirements prescribed by IEC 60512-99-002 |
| <b>PoE Durability</b>  | Supports IEEE 802.3bt Type 4 (90 W) applications greater than 3000 plug to jack mating cycles  |
| <b>Safety Voltage Rating</b>                                 | 150 Vac  |

## Material Specifications

|                                    |                  |
|------------------------------------|------------------|
| <b>Contact Base Material</b>       | Beryllium copper |
| <b>Contact Plating Material</b>    | Gold             |
| <b>Material Type</b>               | Polycarbonate    |
| <b>Termination Contact Plating</b> | Tin              |

## Mechanical Specifications

|                                      |                                |
|--------------------------------------|--------------------------------|
| <b>Plug Retention Force, minimum</b> | 50 N   11.24 lbf               |
| <b>Plug to Jack Mating Cycles</b>    | Complies to IEC 60603-7 series |

## Environmental Specifications

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Operating Temperature</b> | -10 °C to +60 °C (+14 °F to +140 °F) |
| <b>Storage Temperature</b>   | -40 °C to +70 °C (-40 °F to +158 °F) |
| <b>Flammability Rating</b>   | UL 94 V-0                            |
| <b>Safety Standard</b>       | UL   cUL                             |

## Packaging and Weights

|                           |                   |
|---------------------------|-------------------|
| <b>Included</b>           | Strain relief cap |
| <b>Packaging quantity</b> | 1                 |
| <b>Packaging Type</b>     | Bag               |

## Regulatory Compliance/Certifications

| <b>Agency</b> | <b>Classification</b>  |
|---------------|--|
| CHINA-ROHS    | Below maximum concentration value  |
| RCM           | Compliant to electrical safety & telecommunications requirements   |
| REACH-SVHC    | Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a> |
| ROHS          | Compliant  |
| UK-ROHS       | Compliant  |

