2291216-4 | KJ610-GY



KJ-Series Modular Jack, RJ45, Cat6 Unshielded, Gray

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America

Portfolio NETCONNECT®

Product Type Modular jack

Product Series KJ Series

General Specifications

ANSI/TIA Category 6

Cable Type Unshielded

Color Gray

Conductor Type Solid | Stranded

Integrated Dust Cover Type None

Mounting Hubbell® faceplates | Leviton® faceplates | Panduit®

faceplates

Mounting Note Color matches with KJ-style Gray Faceplates and Surface Mount

Boxes

Outlet Type Keystone

Termination Tool 110 Punchdown tool | SL Termination tool

Termination Type IDC

Transmission Standards ANSI/TIA-568-C.2 | ISO/IEC 11801 Class E

Wiring T568A | T568B

Dimensions

Panel Cutout, recommended 14.79 x 19.31 mm (0.58 x 0.76 in)

Panel Thickness, recommended 1.6 mm | 0.063 in

 Height
 16.13 mm | 0.635 in

 Width
 16.48 mm | 0.649 in

Depth 30.48 mm | 1.2 in



2291216-4 | KJ610-GY

Compatible Insulated Conductor Diameter, maximum 1.27 mm | 0.05 in

Contact Plating Thickness1.27 μmCompatible Conductor Gauge, solid24-22 AWGCompatible Conductor Gauge, stranded26-24 AWG

Electrical Specifications

Remote Powering Fully supports the safe delivery of power over LAN cabling described

by IEEE 802.3bt (Type 4) and complies with the unmating under electrical load requirements prescribed by IEC 60512-99-002

PoE Durability Supports IEEE 802.3bt Type 4 (90 W) applications after 3000 plug to

jack mating cycles

Material Specifications

Contact Base Material Beryllium copper

Contact Plating Material Gold

Material Type Polycarbonate

Mechanical Specifications

Plug to Jack Mating Cycles Complies to IEC 60603-7 series

Environmental Specifications

Flammability Rating UL 94 V-0

Packaging and Weights

Packaging quantity 1
Packaging Type Bag

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



