

SFX-ADM



7-16 DIN Male for 1/2 in SFX-500 cable

OBSOLETE

This product was discontinued on: December 2, 2015

Product Classification

Product Type Wireless and radiating connector

General Specifications

Body Style Straight

Cable Family SFX-500

Inner Contact Attachment Method Captivated

Inner Contact Plating Silver

Interface 7-16 DIN Male

Outer Contact Attachment Method Radial compression

Outer Contact Plating Silver

Pressurizable No

Dimensions

Width 36.07 mm | 1.42 in

Length 51.05 mm | 2.01 in

Diameter 36.07 mm | 1.42 in

Nominal Size 1/2 in

Electrical Specifications

3rd Order IMD at Frequency -115 dBm @ 1800 MHz

3rd Order IMD Test Method Two +43 dBm carriers

SFX-ADM

Return Loss Note	Measurements taken using a .9 m (3 ft) jumper assembly
Average Power at Frequency	870.0 W @ 900 MHz
Cable Impedance	50 ohm
Connector Impedance	50 ohm
dc Test Voltage	2500 V
Inner Contact Resistance, maximum	1.5 mOhm
Insulation Resistance, minimum	5000 MOhm
Operating Frequency Band	0 – 6000 MHz
Outer Contact Resistance, maximum	0.4 mOhm
Peak Power, maximum	15.6 kW
RF Operating Voltage, maximum (vrms)	707 V
Shielding Effectiveness	110 dB

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
0.05–1.0 GHz	1.05	32.26
1.0–2.0 GHz	1.08	28.3
2.0–2.5 GHz	1.1	26.45
2.5–5.0 GHz	1.29	18
5.0–6.0 GHz	1.38	16

Mechanical Specifications

Connector Retention Tensile Force	889.64 N 200 lbf
Connector Retention Torque	2.03 N-m 18.002 in lb
Coupling Nut Proof Torque	50 N-m 442.537 in lb
Coupling Nut Proof Torque Method	IEC 61169-4:9.3.6
Coupling Nut Retention Force	1000 N 224.81 lbf
Coupling Nut Retention Force Method	IEC 61169-4:15.2.6
Insertion Force	199.99 N 44.96 lbf
Insertion Force Method	IEC 61169-4:15.2.4
Interface Durability	500 cycles
Interface Durability Method	IEC 61169-4:17
Mechanical Shock Test Method	IEC 60068-2-27

SFX-ADM

Environmental Specifications

Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-65 °C to +100 °C (-85 °F to +212 °F)
Attenuation, Ambient Temperature	20 °C 68 °F
Average Power, Ambient Temperature	40 °C 104 °F
Average Power, Inner Conductor Temperature	100 °C 212 °F
Corrosion Test Method	IEC 60068-2-11
Immersion Depth	1 m
Immersion Test Mating	Mated
Immersion Test Method	IEC 60529:2001, IP68
Thermal Shock Test Method	IEC 60068-2-14
Vibration Test Method	IEC 60068-2-6

Packaging and Weights

Weight, net	86 g 0.19 lb
--------------------	----------------

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

* Footnotes

Immersion Depth	Immersion at specified depth for 24 hours
------------------------	---