

SFX-ANM

Type N Male A Series for 1/2 in SFX-500 cable



OBSOLETE

This product was discontinued on: December 2, 2015

Product Classification

Product Type Wireless and radiating connector

General Specifications

Body Style Straight

Cable Family SFX-500

Inner Contact Attachment Method Captivated

Inner Contact Plating Gold

Interface N Male

Mounting Angle Straight

Outer Contact Attachment Method Radial compression

Outer Contact Plating Silver

Pressurizable No

Dimensions

Width 20.57 mm | 0.81 in

Length 57.91 mm | 2.28 in

Diameter 20.57 mm | 0.81 in

Nominal Size 1/2 in

Electrical Specifications

3rd Order IMD at Frequency -115 dBm @ 1800 MHz

SFX-ANM

3rd Order IMD Test Method	Two +43 dBm carriers
Return Loss Note	Measurements taken using a .9 m (3 ft) jumper assembly
Average Power at Frequency	600.0 W @ 900 MHz
Cable Impedance	50 ohm
Connector Impedance	50 ohm
dc Test Voltage	2000 V
Inner Contact Resistance, maximum	1 mOhm
Insulation Resistance, minimum	5000 MOhm
Operating Frequency Band	0 – 6000 MHz
Outer Contact Resistance, maximum	0.25 mOhm
Peak Power, maximum	10 kW
RF Operating Voltage, maximum (vrms)	707 V
Shielding Effectiveness	110 dB

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
0.05–1.0 GHz	1.05	32.26
1.0–2.0 GHz	1.08	28.3
2.0–2.5 GHz	1.1	26.45
2.5–5.0 GHz	1.29	18
5.0–6.0 GHz	1.38	16

Mechanical Specifications

Attachment Durability	25 cycles
Connector Retention Tensile Force	889.64 N 200 lbf
Connector Retention Torque	1.4 N-m 12.356 in lb
Coupling Nut Proof Torque	1.7 N-m 15.046 in lb
Coupling Nut Proof Torque Method	IEC 61169-16:9.3.6
Coupling Nut Retention Force	449.98 N 101.16 lbf
Coupling Nut Retention Force Method	IEC 61169-16:9.3.11
Insertion Force	27.98 N 6.29 lbf
Insertion Force Method	IEC 61169-16:9.3.5
Interface Durability	500 cycles
Interface Durability Method	IEC 61169-16:9.5

SFX-ANM

Mechanical Shock Test Method IEC 60068-2-27

Environmental Specifications

Operating Temperature -55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature -65 °C to +100 °C (-85 °F to +212 °F)
Attenuation, Ambient Temperature 20 °C | 68 °F
Average Power, Ambient Temperature 40 °C | 104 °F
Average Power, Inner Conductor Temperature 100 °C | 212 °F
Corrosion Test Method IEC 60068-2-11
Immersion Depth 1 m
Immersion Test Mating Mated
Immersion Test Method IEC 60529:2001, IP68
Moisture Resistance Test Method IEC 60068-2-3
Thermal Shock Test Method IEC 60068-2-14
Vibration Test Method IEC 60068-2-6

Packaging and Weights

Weight, net 64 g | 0.141 lb

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

* Footnotes

Immersion Depth Immersion at specified depth for 24 hours