# 244106A-320



Product Classification

Included

### Flex-Twist Hanger Assembly for WR28

PIUUULI LIASSIIILALIUII	
Product Type	Hanger kit
General Specifications	
Cable Type	Elliptical waveguide
Cables per Hanger	1
Color	Silver
Hanger Type	Flex-Twist hanger
Mounting	4.5 in OD pipe
Dimensions	
Height	7.6 mm   0.299 in
Width	151.9 mm   5.98 in
Length	381 mm   15 in
Waveguide Size	WR28   WG22   R320
Material Specifications	
Material Type	Stainless steel
Mechanical Specifications	
Wind Speed, survival with 1/2 in (12 mm) radial ice	201.167 km/h   125 mph
Environmental Specifications	
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Corrosion Test Method	MIL-F-14072C   MIL-STD-889B
Packaging and Weights	

Clamp | Rubber grommet | Threaded rod

Page 1 of 2



## 244106A-320

#### Packaging quantity

Weight, gross

0.5 kg | 1.102 lb

## Regulatory Compliance/Certifications

Classification

#### Agency

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

1

Page 2 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 2, 2025