

Double Block Hanger for 1/2 in coaxial cable (LDF4) - Hardware Sold Separately (search 243095-SERIES-HARDWARE for options avaliable)

Product Classification

Product TypeHanger kitProduct BrandHELIAX®

Ordering Note ANDREW® standard product (Global)

General Specifications

Cables per Hanger 2
Color Black

Hanger Type Double block hanger

Mounting Mounting hole clearance for 3/8, 16 UNC or M10 threaded rod

Dimensions

Maximum Stack Height 4

 Height
 40.1 mm | 1.579 in

 Width
 33 mm | 1.299 in

 Length
 67.1 mm | 2.642 in

Compatible Cable Diameter Range 15.2–16.3 mm

Compatible Diameter, maximum16.3 mm | 0.642 inCompatible Diameter, minimum15.2 mm | 0.598 in

Nominal Size 1/2 in

Electrical Specifications

 Return Loss Effect, maximum
 0.1 dB

 DTF Effect, maximum
 0.1 dB

Material Specifications



Page 1 of 2

BHD-12

Material Type Engineered plastic

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C}$ to $+85 \,^{\circ}\text{C}$ ($-40 \,^{\circ}\text{F}$ to $+185 \,^{\circ}\text{F}$)

Environmental Strength Capability Double cable weight

UV Resistance, minimum with no degradation ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

 Height, packed
 3.8 cm | 1.496 in

 Width, packed
 17.8 cm | 7.008 in

 Length, packed
 25.4 cm | 10 in

Packaging quantity 10

Weight, gross 0.37 kg | 0.816 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.andrew.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

