


# SF-10203NNNNXABB | FBT 1X2 97/03 250UM NO CONN

---



FBT Coupler, singlemode, 1x2 FBT, 97/03 split ratio, 0.250 mm cable, no connectors

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   China   EMEA   India   Latin America   North America
<b>Product Type</b>	Bare splitter

## General Specifications

<b>Device Type</b>	Component, tubular
<b>Functionality</b>	Splitting
<b>Technology Type</b>	Fused biconic tapered
<b>Distribution Type</b>	1 x 2 splitter
<b>Interface, Input</b>	Stub tail
<b>Interface, Output</b>	Stub tail
<b>Split Ratio</b>	97/3
<b>Splitter, quantity</b>	1

## Dimensions

<b>Height</b>	3.2 mm   0.126 in
<b>Length</b>	55 mm   2.165 in
<b>Pigtail Length, Input</b>	2.5 m   8.202 ft
<b>Pigtail Length, Output</b>	2.5 m   8.202 ft
<b>Pigtail Diameter, Input</b>	0.25 mm   0.01 in
<b>Pigtail Diameter, Output</b>	0.25 mm   0.01 in

## Optical Specifications

<b>Fiber Type</b>	G.657.A1
<b>Directivity, minimum</b>	55 dB
<b>Polarization Dependent Loss, maximum</b>	0.2 dB

# SF-10203NNNNXABB | FBT 1X2 97/03 250UM NO CONN

---

<b>Wavelength Range</b>	1260–1360 nm   1420–1625 nm
<b>Insertion Loss, Primary Output, maximum</b>	0.4 dB
<b>Insertion Loss, Secondary Output, maximum</b>	17.9 dB
<b>Return Loss, Splitter, minimum</b>	55 dB

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +70 °C (-40 °F to +158 °F)
<b>Relative Humidity</b>	5%–95%, non-condensing

## Packaging and Weights

<b>Packaging quantity</b>	1
---------------------------	---

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant

