PPLUQGRSNSNR

Propel ULL Singlemode Cabled Module, 1x16 duplex SN Propel module on End A to 1x16 on End B, 16 fiber Plenum Patchcord, Method B Enhanced

- This component requires 4 of the 12 lanes on the Propel Panel blade
- Ultra-low loss (ULL) with Method B Enhanced polarity
- End A module can be installed from rear of panel
- Serialized QR code provides easy access to factory optical test results

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio SYSTIMAX®

Product Type Fiber cabled module

Product Brand Propel
Product Series PPL

Ordering Note End B module is the same module as End A | For lengths greater than 999 ft (304 m),

orders must be in meters | Maximum length is 400 meters

General Specifications

Configuration Type PROPEL Module to PROPEL Module

 Cable Color
 Yellow

 Cable Type
 Patch cord Plenum

Interface, front SN/UPC

Interface Feature, front Duplex | Shuttered

 Interface Color, front
 Blue

 Interface, rear
 SN/UPC

Interface Feature, rear Duplex | Shuttered

Module Size, end A24 fiberModule Size, end B24 fiber

Module Quantity, end A 1

Module Quantity, end B 1

Polarity Method B Enhanced (ULL)

Total Fibers, quantity 16

Total Ports, quantity, front 8

COMMSCOPE®

PPLUQGRSNSNR

Dimensions

 Height
 11 mm | 0.433 in

 Width
 196 mm | 7.717 in

 Depth
 170 mm | 6.693 in

Breakout Length, end B 23 in

Cable Assembly Length Range (m) 1 - 400

Cable Assembly Length Range (ft) 2 - 999

Ordering Tree



Optical Specifications

Fiber Mode Singlemode

Fiber Type OS2
Insertion Loss, maximum 0.6 dB

Environmental Specifications

Qualification Standards IEC 61753-1 | TIA-568.3-D

Safety Standard c-UL-us

Packaging and Weights

Packaging quantity 1

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

ROHS Compliant/Exempted

COMMSCOPE®

PPLUQGRSNSNR

UK-ROHS

Compliant



Included Products

760249691 P-016-MP-8G1-F30YL Fiber indoor cable, Plenum MPO Light Duty for Patchcords, 16 fiber, Singlemode G.657.A2/B2, Feet jacket marking, Yellow jacket color

