

6		7	8			9	0			
						REVIS CMO 40167074CMO 40178757CMO	I ON S D A T E 3 I - JUL - 2023 06 - SEP - 2023	APPROVED IDM MAM A		
	DETAIL A TYP (3) PLACES T-BOLT STRAIGHT					PARTS LIST				
	/			I		DESCRIPTION		QTY		
						CANTILEVER	CANTILEVER BRACKET			
	T - SLOT				2	BRACKET	CLIP	I C		
	BRACKET				3	BOTTOM BR	ACKET			
					4	SPLIT N	NUT	2		
QUICK KNOB					5	QUIC KNOB A SCREW, THREA		3		
								E		
						GS-HETR-F-12MM GS-HETR-F-16MM	121			
					FGS-HETR-F-1/2					
					F	GS-HETR-F-5/8	5 / 8	8 " F		
						ATALOG NUMBER	ROD DIA	AMETER		
>	TOLERANCES . XX:±&TOL_XX . XXX:±&TOL_XX . XXX:±&TOL_XXX ANGULAR:±&TOL_ANG					MMSCOPE, INC.				
		INTESS ATHEDWISE SDECTETED	DRAFTER CRAIG ZELASKO CHECKER RUBEN ARVILLA ENGINEER DEREK DERKS CMO 40178757CM SURFACES AUTH GRP: ISPF	0	TITLE I.D. SIZE A 2 ODEL		5 THRD ROD M 58724_A			
	onfidential prietary property of COMMSCOPE, II red in writing by COMMSCOPE, INC.	NC.	V VERS 0 8		<u>STATUS</u>	REVISION VERSION 02 9	STATUS REVIS RE D IO			

	2		3		4	5	¥
COMPLETED BRACKET (SEE	ASSEMBLY SHEET I)						
Q					5		
Molding fitting ref							
						AND	
NOTE :							
- SCREW INSTALLAT	ION INSTRUCTIO	ONS: (FOR	MOUNTING	TO FITTING	GS ONLY)		
I. INSERT SCR ON MOLDED	EW THROUGH BRA FITTING. TIGHT						
NOTE - IF MOUNT POSITION) FITTINGS, Ely 3/8" lo	BRACKET	MUST BE			

