SFG23HDXL-14-BNH



G23HDX High Capacity Sector Frame with extended 5' standoff for sites requiring increased sector to sector antenna spacing . 2 7/8in OD x 14.5ft face. Antenna pipes sold separately.

Product Classification

Product Type High capacity Tower sector frame

Product Series G2

General Specifications

Mounting Angle 60°, 203.2 mm (8 in) | Straight or tapered legs up to 203.2 mm (8 in) OD

Patent Number For patents see: www.cs-pat.com

Pipe, quantity 0
Sectors, quantity 1

Tower Taper Non-tapered | Tapered

Dimensions

 Height
 838.2 mm | 33 in

 Face Width
 4.42 m | 14.5 ft

Width 4,419.6 mm | 174 in

Face Support Pipe Diameter 73.025 mm | 2.875 in

Mounting Diameter, maximum203.2 mm | 8 inMounting Diameter, minimum38.1 mm | 1.5 in

 Pipe Outer Diameter
 73.025 mm | 2.875 in

 Stand-off Distance
 1,549.4 mm | 61 in

Material Specifications

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating For Specifications, please contact steelproducts@commscope.com or call 800-255-1479

Page 1 of 2



SFG23HDXL-14-BNH

Wind Rating Test Method TIA/EIA-222-G

Packaging and Weights

Included Frame | Stiff arms (2) | Tower attachment

Packaging quantity 1

Weight, net 327.857 kg | 722.8 lb

* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

