# 760257280 | UKJ600-OR



KJ-Series Modular Jack, RJ45, Cat6 Unshielded, Orange

## Product Classification

| Regional Availability                                 | North America   |
|---|---|
| Portfolio   | Uniprise®   |
| Product Type  | Modular jack  |
| Product Series  | UKJ Series  |
| General Specifications                                |   |
| ANSI/TIA Category                                     | 6   |
| Cable Type  | Unshielded  |
| Color   | Orange  |
| Conductor Type  | Solid   Stranded  |
| Integrated Dust Cover Type                            | None  |
| Termination Type                                      | IDC   |
| Wiring  | T568A   T568B   |
| Dimensions  |   |
| Compatible Conductor Gauge, solid                     | 22 AWG   24 AWG   |
| Compatible Conductor Gauge, stranded                  | 24 AWG   26 AWG   |
| Electrical Specifications                             |   |
| Contact Resistance Variation, maximum                 | 20 mOhm   |
| Contact Resistance, maximum                           | 100 mOhm  |
| Current Rating at Temperature                         | 1.5 A @ 20 °C   1.5 A @ 68 °F   |
| Dielectric Withstand Voltage, RMS, conductive surface | 1,500 Vac @ 60 Hz   |
| Dielectric Withstand Voltage, RMS, contact-to-contact | 1,000 Vac @ 60 Hz   |
| Insulation Resistance, minimum                        | 500 MOhm  |
| Remote Powering                                       | Fully supports the safe delivery of power over LAN cabling described by IEEE 802.3bt (Type 4) and complies with the |

Page 1 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: June 12, 2024



# 760257280 | UKJ600-OR

|                               | unmating under electrical load requirements prescribed by IEC 60512-99-002             |
|-------------------------------|--|
| PoE Durability                | Supports IEEE 802.3bt Type 4 (90 W) applications after 3000 plug to jack mating cycles |
| Material Specifications       |  |
| Contact Plating Material      | Precious metals  |
| Material Type                 | High-impact, flame retardant, thermoplastic   PC+ABS                                   |
| Termination Contact Plating   | Nickel   |
| Mechanical Specifications     |  |
| Plug Retention Force, minimum | 133 N   29.9 lbf   |
| Plug to Jack Mating Cycles    | Complies to IEC 60603-7 series   |
|                               |  |
| Environmental Specifications  |  |
| Operating Temperature         | -10 °C to +60 °C (+14 °F to +140 °F)   |
| Storage Temperature           | -40 °C to +70 °C (-40 °F to +158 °F)   |
| Relative Humidity             | Up to 95%, non-condensing  |

Flammability Rating

Safety Standard

### Packaging and Weights

#### Packaging quantity

1

UL 94 V-0

UL | cUL

## Regulatory Compliance/Certifications

| Agency        | Classification   |
|---------------|--|
| CHINA-ROHS    | Below maximum concentration value  |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC    | Compliant as per SVHC revision on www.commscope.com/ProductCompliance          |
| ROHS          | Compliant  |
| UK-ROHS       | Compliant  |
|               |  |

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: June 12, 2024

